

TRUE GAIN ANTENNAS

All The Signal...

True Gain Yagi 900 MHz ISM band antennas are expertly engineered and manufactured to the highest standards of quality and performance. Antennas include mounting bracket and hardware for up to 2" O.D. masts.


Applications:

- Broadband networks and service
- Canopy radios
- Point to multipoint




Features –


- **Lifetime Warranty:** Materials and Workmanship
- **Boom Lengths:**
 - 41.3" (104.8 cm)
 - 50.9" (129.4 cm)
 - 79.4" (201.7 cm)
- **Maximum Widths:**
 - 6.5" (16.6 cm)
 - 6.5" (16.6 cm)
 - 6.4" (16.2 cm)
- **Weights:**
 - 1 lb. 5 oz. (0.60 kg)
 - 1 lb. 10 oz. (0.74 kg)
 - 2 lbs. 1 oz. (0.94 kg)
- **Rugged Environmental Resistant Design**
- **Environment:**
 - Operational: 100 mph (161 Km/hr.)
 - Survival: 100 mph (161 Km/hr.)
- **Color:** Light gray powder coat, optional end plugs
- **Connection:** Low loss 36" coax, N or SMA



TG-Y915-14



TG-Y915-15



TG-Y915-17

Electrical Specifications:

Model	Frequency (MHz)	Polarization	Gain (dBi) typical	Beamwidth (°) -3 dB @ 915 MHz	F/B (dB) @ 915 MHz	VSWR max.	Elements
TG-Y915-14	900 - 928	Hz. / Vert.	14.3	33.8	17	1.19:1	10
TG-Y915-15	900 - 928	Hz. / Vert.	15.2	26.7	18	1.26:1	12
TG-Y915-17	900 - 928	Hz. / Vert.	17.3	21.6	21	1.29:1	20

All specifications subject to change without notice